



## MATERIAL SAFETY DATA SHEET

### Section 1 - Identification of Chemical Product and Company

**Substance:** Blend of liquid hydrocarbon and emulsifiers.  
**Trade Name:** Norsolve No 1  
**Product Use:** Degreaser.  
**Creation Date:** September, 2003  
**Revision Date:** August, 2007

### Section 2 - Hazards Identification

#### Statement of Hazardous Nature

This product is classified as: Hazardous according to the criteria of ASCC Australia.

Dangerous according to the Australian Dangerous Goods (ADG) Code.

**Risk Phrases:** R10, R65, R66. Flammable. Harmful: May cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

**Safety Phrases:** S16, S37, S46, S24/25. Keep away from sources of ignition - No smoking. Wear suitable gloves. If swallowed, contact a doctor or Poisons Information Centre immediately and show this container or label. Avoid contact with skin and eyes.

**SUSDP Classification:** S5

**ADG Classification:** Class 3 (FLAMMABLE LIQUID, N.O.S.)

**UN Number:** 1993

### Emergency Overview

**Physical Description & colour:** Clear colourless liquid.

**Odour:** Odour of mineral turpentine.

**Major Health Hazards:** if aspirated, may cause lung damage. Prolonged and repeated skin contact may cause dermatitis due to defatting effect.

### Potential Health Effects

#### Inhalation

**Short term exposure:** Available data indicates that this product is not harmful. In addition product is unlikely to cause any discomfort or irritation.

**Long Term exposure:** No data for health effects associated with long term inhalation.

#### Skin Contact:

**Short term exposure:** Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be irritating, but is unlikely to cause anything more than mild transient discomfort.

**Long Term exposure:** No data for health effects associated with long term skin exposure.

#### Eye Contact:

**Short term exposure:** This product is believed to be mildly irritating, to eyes, but is unlikely to cause anything more than mild transient discomfort.

**Long Term exposure:** No data for health effects associated with long term eye exposure.

#### Ingestion:

**Short term exposure:** Because of the low viscosity of this product, it may directly enter the lungs if swallowed, or if subsequently vomited. Once in the lungs, it is very difficult to remove and can cause severe injury or death. However, this product may be irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

# MATERIAL SAFETY DATA SHEET

**Long Term exposure:** No data for health effects associated with long term ingestion.

## **Carcinogen Status:**

**ASCC:** No significant ingredient is classified as carcinogenic by ASCC.

**NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** No significant ingredient is classified as carcinogenic by IARC.

---

## **Section 3 – Composition/Information on Ingredients**

<b>Ingredients</b>	<b>CAS No</b>	<b>Conc,%</b>	<b>TWA (mg/m<sup>3</sup>)</b>	<b>STEL (mg/m<sup>3</sup>)</b>
Mineral turpentine	8032-32-4	80-90	not set	not set
Other non hazardous ingredients	secret	to 100	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that should not be exceeded for more than 15 minutes and should not be repeated for more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

---

## **Section 4 - First Aid Measures**

### **General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia and is available at all times. Have this MSDS with you when you call.

**Inhalation:** First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

**Skin Contact:** Irritation is unlikely. However, if irritation does occur, flush with lukewarm, gently flowing water for 5 minutes or until chemical is removed. If in doubt obtain medical advice.

**Eye Contact:** Quickly and gently blot or brush product away. Flush the contaminated eye(s) with lukewarm, gently flowing water until the product is removed or until irritation has ceased, while holding the eyelid(s) open. Obtain medical advice if irritation becomes painful or lasts more than a few minutes.

**Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

---

## **Section 5 – Fire Fighting Measures**

**Fire and Explosion Hazards:** This product is classified as flammable. There is a moderate risk of an explosion from this product if commercial quantities are involved in a fire. Firefighters should take care and appropriate precautions. Any explosion will likely spread the fire to surrounding materials. Water spray may be used to cool drums involved in a fire, reducing the chances of an explosion. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Preferred extinguishing media are carbon dioxide, dry chemical, foam. Foam is the preferred medium for large fires.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade.

**Flash point:** Expected to be in the range 30-60°C

**Upper Flammability Limit:** No data.

**Lower Flammability Limit:** No data.

**Autoignition temperature:** No data.

**Flammability Class:** Flammable

---

## **Section 6 – Accidental Release Measures**

**Accidental release:** In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Immediately call the Fire Brigade. As a minimum, wear overalls, goggles and gloves. Suitable materials for protective clothing include rubber, PVC. Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Avoid using sawdust or other combustible material. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. This material may be suitable for approved landfill. Ensure legality of

# MATERIAL SAFETY DATA SHEET

disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

## Section 7 – Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this class of poison. Store in a cool, well ventilated area, and make sure that surrounding electrical devices and switches are suitable. Check containers periodically for leaks. Containers should be kept closed in order to minimise contamination and possible evaporation. Make sure that the product does not come into contact with substances listed under "Materials to avoid" in Section 10. If you keep more than 1000L of flammable liquids of Packaging Group III, you probably require a license to do so. If you have any doubts, we suggest you contact your licensing authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## Section 8 Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Industrial Clothing: **AS2919**, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

### Exposure Limits

#### TWA (mg/m<sup>3</sup>)

#### STEL (mg/m<sup>3</sup>)

Exposure limits have not been established by ASCC for any of the significant ingredients in this product.

**Ventilation:** No special ventilation requirements are normally necessary for this product. However make sure that the work environment remains clean and that vapours and mists are minimised.

**Eye Protection:** Eye protection such as protective glasses or goggles is recommended when this product is being used.

**Skin Protection:** You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: rubber, PVC.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Safety deluge showers should be provided near to where this product is being used.

## Section 9 - Physical and Chemical Properties:

<b>Physical Description &amp; colour:</b>	Clear colourless liquid.
<b>Odour:</b>	Odour of mineral turpentine.
<b>Boiling Point:</b>	Not available.
<b>Freezing/Melting Point:</b>	No specific data. Liquid at normal temperatures.
<b>Volatiles:</b>	No specific data. Expected to be low at 100°C.
<b>Vapour Pressure:</b>	No data.
<b>Vapour Density:</b>	No data.
<b>Specific Gravity:</b>	No data.
<b>Water Solubility:</b>	Negligible.
<b>pH:</b>	No data.
<b>Volatility:</b>	No data.
<b>Odour Threshold:</b>	No data.
<b>Evaporation Rate:</b>	No data.
<b>Coeff Oil/water distribution:</b>	No data.
<b>Autoignition temp:</b>	No data.

## Section 10 – Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** This product should be kept in a cool place, preferably below 30°C. Keep away from sources of sparks or ignition. Handle and open containers carefully. Any electrical equipment in the area of this product should be flame proofed.

# MATERIAL SAFETY DATA SHEET

**Incompatibilities:** oxidising agents.

**Fire Decomposition:** Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product is unlikely to undergo polymerisation processes.

## Section 11 – Toxicological Information

**Target Organs:** There is no data to hand indicating any particular target organs.

## Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Mineral Turpentine	Conc≥10% : R65

## Section 12 – Ecological Information

This product is biodegradable. It will not accumulate in the soil or water or cause long term problems.

## Section 13 – Disposal Considerations

**Disposal:** Containers should be emptied as completely as practical before disposal. If possible, recycle containers either in-house or send to recycle company. If this is not practical, send to a commercial waste disposal site. Please do NOT dispose into sewers or waterways.

## Section 14 – Transport Information

**ADG Code:** 1993, FLAMMABLE LIQUID, N.O.S.

**Hazchem Code:** 3[Y]

**Special Provisions:** SP109, SP185, SP274

**Dangerous Goods Class:** Class 3, Flammable liquids.

**Packaging Group:** III

**Packaging Method:** 3.8.3, RT1

Class 3 Flammable Liquids shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 2.1 (Flammable Gases where flammable liquids and flammable gases are both in bulk), 2.3 (Toxic Gases), 4.2 (Spontaneously Combustible Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances, except Flammable Liquid is nitromethane), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases except where the Flammable Liquids and Flammable Gases are in bulk), 2.2 (Non-Flammable Non-Toxic Gases), 4.1 (Flammable Solids), 4.3 (Dangerous When Wet Substances), 6 (Toxic Substances, except where Flammable Liquid is nitromethane), 8 (Corrosive Substances), 9 (Miscellaneous Dangerous Goods), Foodstuffs or foodstuff empties.

## Section 15 – Regulatory Information

**AICS:** All of the significant ingredients in this formulation are to be found in the public AICS Database. The following ingredients: Mineral turpentine, are mentioned in the SUSDP as liquid hydrocarbons.

## Section 16 – Other Information

This MSDS contains only safety-related information. For other data see product literature.

### Acronyms:

<b>ADG Code</b>	Australian Code for the Transport of Dangerous Goods by Road and Rail
<b>AICS</b>	Australian Inventory of Chemical Substances
<b>CAS number</b>	Chemical Abstracts Service Registry Number
<b>Hazchem Number</b>	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
<b>IARC</b>	International Agency for Research on Cancer
<b>ASCC</b>	<b>Office of the Australian Safety and Compensation Council</b>
<b>NOS</b>	Not otherwise specified
<b>NTP</b>	National Toxicology Program (USA)
<b>R-Phrase</b>	Risk Phrase
<b>SUSDP</b>	Standard for the Uniform Scheduling of Drugs & Poisons
<b>UN Number</b>	United Nations Number

### Contact Points:

Issued by: North Queensland Chemicals & Paints

Product Name: Norsolve No 1

Phone: (07)4951 3988

Page: 4 of 5

This MSDS last updated: August, 2007

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

# MATERIAL SAFETY DATA SHEET

Mackay: Phone: (07)4951 3988 Fax: (07)4951 1862  
After Hours: (07)4951 0593

**National Poisons Information Centre: Dial 13 1126 (from anywhere in Australia)**

Please read all labels carefully before using product.

This MSDS summarises North Queensland Chemicals & Paints best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. The responsibility for products sold is subject to our standard terms and conditions, a copy of which is available on request.

This MSDS is prepared in accord with the ASCC document "National Code of Practice for the Preparation of Material Safety Data Sheets" 2nd Edition [NOHSC:2001(2003)]  
Copyright © Kilford & Kilford Pty Ltd, August, 2007.

<http://www.kilford.com.au> Phone (02)9251 4532